

Fall Arrest Block

Tiger TIB Fall Arrest Retractable Lifelines / Inertia Reels are designed to reduce vertical impact force on the body caused by falling from height. They are used to provide semi-permanent fall protection. The lifeline tension allows the user to move freely around the work area.

PPE Category III Retractable Type Fall Arrestor - wire and webbing types available.

Wire type

Available with 6m, 10m, 15m, 20m, 30m (20 ft, 33ft, 49ft, 66ft, 98ft) wire rope lengths.

- Lightweight, compact and durable
- Triple pawl brake system with energy dissipating mechanism
- Side cable exit for smooth operation and reduced cable wear
- 150kg (330lbs) capacity for operator and tools
- Top anchor point with built-in swivel-limits lifeline twisting
- Supplied with screw gate carabiner for fitting to a suitable anchor point
- Top scaffold hook available as an option
- Lower self-locking snap hook and swivel with built-in impact indicator for connecting directly to the safety harness
- All fittings meet EN 362:2002
- Buffer spring at cable exit protects block and allows for smooth operation
- Fully serviceable by an approved Service Agent/Center
- High strength ABS (thermoplastic) casing
- Ergonomic carrying handle makes transport, set-up and storage easy and safe
- Side case with metal bush for shaft housing
- Minimum static strength 15kN
- Easy to inspect
- 4.8mm galvanised wire rope
- Supplied with pull down cord
- Conforms to EN 360:2002 EC Notified Body Apave
- Braking force: less than 6kN
- Operating Temperature: -30°C to +50°C (-22°F to +122°F)



Triple pawl brake system

Product Code	Length of wire (m, ft)	Net Weight (lb)
TIB-06	6, 20	13.0
TIB-10	10, 33	14.3
TIB-15	15, 49	17.6
TIB-20	20, 66	23.8
TIB-30	30, 98	29.3

Webbing type

Available with 2m, 3.5m and 6m (6.5ft, 11.5ft, and 20ft) webbing lengths

- Lightweight, compact and durable
- Ideal for use in areas where a wire rope could damage fragile items in the work area
- Top anchor point with built-in swivel - limits lifeline twisting (2m and 3.5m models) (6.5ft and 11.5ft)
- Supplied with screw gate carabiner for fitting to a suitable anchor point
- Top scaffold hook available as an option
- 6m (3.2 ft) model complete with lower self-locking snap hook and swivel with built-in impact indicator
- 2m and 3.5m (6.5ft and 11.5ft) models with “rip stitch indicator” and ultra lightweight self-locking hook
- All fittings meet EN 362:2002
- 140kg (309 lbs) capacity
- Lightweight aluminium housing for 2m and 3.5m (6.5 ft and 11.5ft) models
- High Strength ABS (thermoplastic) casing for 6m (19.6ft) model
- Minimum static strength 15kN
- Easy to inspect
- Dyneema webbing
- 3.5m and 6m (11.5ft and 20ft) models supplied with pull down cord
- Conforms to EN 360:2002
- Braking force: less than 6kN
- Operating Temperature: -30°C to +50°C (-22°F to +122°F)



Product Code	Length of webbing (m, ft)	Width of webbing (mm, in)	Net Weight (lb)
TIB-02-W	2, 6.6	25, 0.98	2.53
TIB-035-W	3.5, 11.5	25, 0.98	3.52
TIB-06-W	6, 19.7	20, 0.87	4.41