SF Industrial Winch

• 1t lifting & 2t pulling capacity

- Ratchet handle permits reciprocating handle
 movement in both directions for lifting and lowering
 loads
- Positive load-actuated brake can hold the load in any position
- Gears and brake are fully covered to prevent dust, dirt and rain contamination
- Very low operator effort is required for easy operation
- Ratchet handle accommodates installation in cramped locations such as wall and floor

ng	Ī		
any		<u>4-ø13</u>	Н
	300	156	
ion			00

119.8

150

Uh

224

 \bigcirc

64.3

238

Product Code	Pulling capacity (lbs/kg)	Lifting capacity (lbs/kg)	Hand force required (kg, lb)		Gear ratio	Hub diameter (mm, in)	Handle length (mm,	Unit weight (with handle)	Cable diameter (mm/in)	Cable storage cap.	
	(IDS/RE)		1st Layer	Mid Layer	Last Layer		,,	in)	(kg, lb)		(m, ft)
SF-2200	4400/2000	2200/1000	11, 24.2	13.5, 29.8	16.5, 36.4	22.2:1	Ø80, Ø3.14	300, 11.8	17.5, 38.6	Ø8.0 <i>,</i> Ø5/16	32, 104
SF-2200-2	4400/2000	2200/1000	33.8, 74.5	41.6, 91.7	51, 112.4	7.2:1	Ø80, Ø3.14	300, 11.8	17.5, 38.6	Ø8.0, Ø5/16	32, 104
SF-2200-3	4400/2000	2200/1000	19, 41.9	23.4, 51.6	28.6, 63.0	12.8:1	Ø80, Ø3.14	300, 11.8	17.5, 38.6	Ø8.0, Ø5/16	32, 104

1



214

WINCHING