

Outstanding Durability

CGC

LIFTING CLAMP FOR CONCRETE MATERIAL (Cam Type)

CHECK!



Operation manual & parts drawing

Example of use

⚠ Always lift a load at 2 or more points for safety.



Features


- Ideal for various kinds of concrete materials like U shaped gutters, U flumes, L shaped panels, boards.
- New cam design with 4 adjustable positions, allowing outstanding durability.
- The releasing lock can be easily set and released by a single action with the hook plate.




CGC250




CGC500



CGC250



CGC500



CGC1000

* Dimensions with concrete material at max. thickness.

Item No.	Rated capacity (lb)	Clamp range (in)	N.W. (lb)
CGC250	551.16	1.18~6.30	13.23
CGC500	1102.31	1.18~6.30	26.46
CGC1000	2204.62	1.18~7.09	57.32

Special Rubber Pad Type

CGC-N

LIFTING CLAMP FOR CONCRETE MATERIAL (Pad Type)


CHECK!



Operation manual & parts drawing

Example of use



⚠ Always lift a load at 2 or more points for safety.



CGC250N



CGC500N



CGC 250N


CGC 500N

* Dimensions with concrete material at max. thickness.


Item No.	Rated capacity (lb)	Clamp range (in)	N.W. (lb)
CGC250N	551.16	1.18~5.51	13.23
CGC500N	1102.31	1.18~5.51	26.46

RELEASE & LOCK MECHANISM OPERATION


With CGC and CGC-N clamps, when you lock the hook plate, the releasing lock mechanism allows easy set or remove of the workpiece.




Land the clamp and lock the hook plate to set the clamp in release position.




Position the opened clamp above the workpiece.




Lay down the clamp and set it on the workpiece.



Unlock the hook plate to set the clamp in lifting position. Hoist the crane hook to lift the workpiece.



Land the workpiece at the target place. At that time, the hook plate gets locked automatically.



Hoist again the crane to remove the clamp, in the release position, from the workpiece.

Features

- Ideal for various kinds of concrete materials like U shaped gutters, U flumes, L shaped panels, boards.
- The spike design of the special rubber pads allows to grip firmly the load (can also be used as non-marring type).
- The releasing lock can be easily set and released by a single action with the hook plate.

* Parts drawings and operation manuals can be downloaded from our website.

● For all the appendix, please refer to P.54 ~56